



Data

• Operation control	ON/OFF with LED indicator, white balance, window function, preset function with three selectable basic setups - all in OSD menu modifiable, brightness adjustment with OSD indicator
• Camera controller	Camera head: white balance, function key Outputs: 1 x RGB Sub-D 2 x S-Video (Y/C) 1 x Video (FBAS) 1 x 3.5 mm cinch for remote control
• Camera head	Image sensor: 3 x 1/3" CCD Image resolution lines: 750 (H) x 430 (V) PAL 750 (H) x 350 (V) NTSC Image resolution act. pixels: 440,000 (PAL)/380,000 (NTSC) Light sensitivity: 5 Lx/f = 2.2 Endoscope coupler: Standard eye piece, C-mount, detachable Focal length TV adapter: f = 23 mm
• Disinfection/Sterilisation	Camera head soakable in liquids, suitable for disinfection, compatible to Steris® and Sterrad®
• System	Acc. guideline Med. Prod. 93/42 EWG Class 1 Electromagn. compatibility: EN 60601-1 Classification: BF/CE mark Power connection: 100-250 V AC, 50/60 Hz Power consumption: 25 VA
• Dimensions/Weight	Camera station: 360 x 88 x 320 mm (W x H x D) Camera head and adapter: 165 x 50 mm (L x ø) Camera cable: 3 m Weight: approx. 4.1 kg

Item numbers

05.9090s.m1	FlexiScope C33001
05.9090s.m1.NTSC	FlexiScope C33001, NTSC